

IP Box Camera



Main Stream Product Line


Model Name	CAM-5200 Series	CAM-5220 Series	CAM-5300 Series	CAM-5320 Series
Type	IP indoor* camera	IP indoor* camera	IP indoor* camera	IP indoor* D/N camera
Image Sensor	1/3" SuperHAD CCD	1/3" EXviewHAD CCD	1/3" SuperHAD CCD	1/3" EXviewHAD CCD
Day/Night	N/A	Yes	N/A	Yes
Mechanical IR Cut Filter	N/A	Yes	N/A	Yes
Lens	Changeable (CS / C mount)	Changeable (CS / C mount)	Changeable (CS / C mount)	Changeable (CS / C mount)
Min. Illumination	0.15 Lux	0.05 Lux	0.15 Lux	0.05 Lux
Compression	MPEG-4 ASP	MPEG-4 ASP	MPEG-4 ASP	MPEG-4 ASP
Max. Video Resolution vs Frame Rate	720 x 480 at 30 fps (NTSC) 720 x 576 at 25 fps (PAL)	720 x 480 at 30 fps (NTSC) 720 x 576 at 25 fps (PAL)	720 x 480 at 30 fps (NTSC) 720 x 576 at 25 fps (PAL)	720 x 480 at 30 fps (NTSC) 720 x 576 at 25 fps (PAL)
FPS (NTSC/PAL)	30/25 at all resolution	30/25 at all resolution	30/25 at all resolution	30/25 at all resolution
Audio	1-way	1-way	N/A	N/A
Failover	Yes	Yes	Yes	Yes
Alarm Input/Output	1/1	1/1	1/1	1/1
Motion Detection	Yes (hardware)	Yes (hardware)	Yes (hardware)	Yes (hardware)
Analog Video Output	Yes	Yes	Yes	Yes
Multi-stream	Up to 4 configurable frame rate/bit rate stream for preview and recording	Up to 4 configurable frame rate/bit rate stream for preview and recording	Up to 4 configurable frame rate/bit rate stream for preview and recording	Up to 4 configurable frame rate/bit rate stream for preview and recording
Protocol	TCP, UDP, RTP, RTSP	TCP, UDP, RTP, RTSP	TCP, UDP, RTP, RTSP	TCP, UDP, RTP, RTSP
Ethernet Networks	10/100 Base-T x2 for LAN/WAN	10/100 Base-T x2 for LAN/WAN	10/100 Base-T x2 for LAN/WAN	10/100 Base-T x2 for LAN/WAN
Power	DC 12 V	Yes (CAM-5200)	Yes (CAM-5300)	Yes (CAM-5320)
	DC 12 V / PoE	Yes (CAM-5201)	Yes (CAM-5221)	Yes (CAM-5321)
	DC 12 V / AC 24 V	--	--	Yes (CAM-5322)

* Outdoor application requires weather-proof housing.

IP Cube Camera



Model Name	ACM-4100 Series
Type	IP indoor cube camera
Image Sensor	1/4" SuperCMOS Sensor
Day/Night	N/A
Mechanical IR Cut Filter	N/A
IR LED	N/A
Lens	Fixed lens, f=4.2 mm
Min. Illumination	0.1 Lux at F1.8
Compression	MPEG-4, MJPEG selectable
Max. Video Resolution vs Frame Rate	640 x 480 at 30 fps (NTSC) 640 x 480 at 25 fps (PAL)



IP Box Camera



Entry Level Product Line

Model Name	ACM-1100 Series	ACM-1111 Series	ACM-1311 Series	ACM-1430 Series
Type	IP indoor* camera	IP indoor* D/N IR camera	IP indoor* D/N IR camera	IP outdoor D/N IR camera
Image Sensor	1/4" SuperCMOS Sensor	1/4" SuperCMOS Sensor	1/3" SuperHAD CCD	1/3" SuperHAD CCD
Day/Night	N/A	Yes	Yes	Yes
Mechanical IR Cut Filter	N/A	Yes	N/A	Yes
IR LED	N/A	Yes	Yes	Yes
Lens	Fixed lens, f=3.8 mm	Fixed lens, f=3.8 mm	Fixed lens, f=4.3 mm	Vari-focal, f=3.8 ~ 9.5 mm
Min. Illumination	0.1 Lux at F2.0	0 Lux at F2.0(IR LED ON)	0 Lux at F2.0(IR LED ON)	0 Lux at F1.2(IR LED ON)
Compression	MPEG-4, MJPEG selectable	MPEG-4, MJPEG selectable	MPEG-4, MJPEG selectable	MPEG-4, MJPEG selectable
Max. Video Resolution vs Frame Rate	640 x 480 at 30 fps (NTSC) 640 x 480 at 25 fps (PAL)	640 x 480 at 30 fps (NTSC) 640 x 480 at 25 fps (PAL)	720 x 480 at 30 fps (NTSC) 720 x 576 at 25 fps (PAL)	720 x 480 at 30 fps (NTSC) 720 x 576 at 25 fps (PAL)
FPS (NTSC/PAL)	30/25 at all resolution	30/25 at all resolution	30/25 at all resolution	30/25 at all resolution
Audio	2-way	2-way	2-way	2-way
Failover	N/A	N/A	N/A	N/A
Alarm Input/Output	N/A	N/A	N/A	N/A
Motion Detection	Yes (hardware)	Yes (hardware)	Yes (hardware)	Yes (hardware)
Analog Video Output	Yes	Yes	Yes	Yes
Multi-stream	Up to 2 configurable frame rate/bit rate stream for preview and recording	Up to 2 configurable frame rate/bit rate stream for preview and recording	Up to 2 configurable frame rate/bit rate stream for preview and recording	Up to 2 configurable frame rate/bit rate stream for preview and recording
Protocol	TCP, UDP, RTP, RTSP	TCP, UDP, RTP, RTSP	TCP, UDP, RTP, RTSP	TCP, UDP, RTP, RTSP
Ethernet Networks	10/100 Base-T x1 for LAN/WAN	10/100 Base-T x1 for LAN/WAN	10/100 Base-T x1 for LAN/WAN	10/100 Base-T x1 for LAN/WAN
Environmental Casing	--	--	--	IP66 weatherproof casing
Power	DC 12 V	Yes (ACM-1100)	--	--
	DC12V/ PoE	Yes (ACM-1101)	Yes (ACM-1111)	Yes (ACM-1311)
	DC 12 V / AC 24 V	--	--	--
				Yes (ACM-1432)

* Outdoor application requires weather-proof housing.

IP Cube Camera

FPS (NTSC/PAL)		30/25 at all resolution
Audio		2-way
Failover		N/A
Alarm Input/Output		N/A
Motion Detection		Yes (hardware)
Analog Video Output		No
Multi-stream		Up to 2 configurable frame rate/bit rate stream for preview and recording
Protocol		TCP, UDP, RTP, RTSP
Ethernet Networks		10/100 Base-T x1 for LAN/WAN
Power	DC 3.3 V	Yes (ACM-4100)

* All specifications are subject to change without notice.

* All brand names and registered trademarks are the property of their respective owners.

www.acti.com

