

IP Cube Camera



Model Name	ACM-4000	ACM-4001
Type	IP indoor cube camera	IP indoor cube camera
Image Sensor	1/3" Micron Progressive Scan CMOS	1/3" Micron Progressive Scan CMOS
Day/Night	N/A	N/A
Mechanical IR Cut Filter	N/A	N/A
IR LED	N/A	N/A
Lens	Fixed lens, f= 4.2mm/F1.8 Fixed iris	Fixed lens, f= 4.2mm/F1.8 Fixed iris
Min. Illumination	0.5 Lux at F1.0	0.5 Lux at F1.0
Compression	MPEG-4, MJPEG selectable	MPEG-4, MJPEG selectable
Max. Video Resolution vs Frame Rate	640 x 480 at 30 fps	640 x 480 at 30 fps
FPS (NTSC/PAL)	30 at all resolution	30 at all resolution
Audio	2-way	2-way
Failover	N/A	N/A
Alarm Input/Output	N/A	N/A
Motion Detection	Yes (hardware)	Yes (hardware)
Analog Video Output	N/A	N/A
Multi-stream	Up to 2 configurable frame rate/ bit rate streams for preview and recording	Up to 2 configurable frame rate/ bit rate streams for preview and recording
Protocol	TCP, UDP, RTP, RTSP, PPPoE, 3GPP	TCP, UDP, RTP, RTSP, PPPoE, 3GPP
Ethernet Networks	10/100 Base-T x1 for LAN/WAN	10/100 Base-T x1 for LAN/WAN
Power Requirement	DC 3.3 V	Yes
	DC 12V / PoE	N/A
		Yes

* All specifications are subject to change without notice.

* All brand names and registered trademarks are the property of their respective owners.